

KOCMO Cross /Cross																
BJ				2006												
Größe	Size			50	51	52	53	54	55	56	57	58	59	60		
Sitzrohr	Seattube	Durchmesser	Diameter	mm	32	32	32	32	32	32	32	32	32	32		
		Länge CTT	Length CTT	mm	530	540	550	560	570	580	590	600	610	620	630	
		Länge CTC	Length CTC	mm	500	510	520	530	540	550	560	570	580	590	600	
		Winkel °	Angle °	°	74	73.5	73.5	73	73	73	73	73	73	73	73	
Oberrohr	Top Tube	Durchmesser	Diameter	mm	32	32	32	32	32	32	32	32	32	32		
		Länge horizontal	Length horizontal	mm	525	530	535	545	550	565	575	585	595	600	605	
Steuerrohr	Head Tube	Durchmesser	Diameter	mm	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	1 1/8"	
		Winkel °	Angle °	°	71	71.5	71.5	72	72	72	72	72	72	72	72	
		Länge	Length	mm	100	105	113	120	128	138	145	152	165	170	180	
Unterrohr	Down Tube	Durchmesser	Diameter	mm	38	38	38	40	40	40	40	40	40	40		
Sitzstreben	Seat Stay	Durchmesser	Diameter	mm	16	16	16	16	16	16	16	16	16	16		
Kettenstreben	Chain Stay	Durchmesser	Diameter		*	*	*	*	*	*	*	*	*	*		
		Länge	Length	mm	430	430	430	430	430	430	430	430	430	430	430	
Sattelstütze	Seat Post	Durchmesser	Diameter	mm	27,2	27,2	27,2	27,2	27,2	27,2	27,2	27,2	27,2	27,2		
Innenlager	Bottom Bracket	Innenlager-VR-Achse	BB-Center to Front	mm	582	579	585	585	591	606	616	626	636	641	647	
		Innenlager-Absenkung	Bottom Bracket Drop	mm	60	60	60	60	60	60	60	60	60	60	60	
		Gewinde	Threads		BSA	BSA	BSA	BSA	BSA	BSA	BSA	BSA	BSA	BSA	BSA	
Rahmen	Frame	Gabelvorlauf / Einbauhöhe	Fork Rake / Mounting Hight	mm	45 / 400	45 / 400	45 / 400	45 / 400	45 / 400	45 / 400	45 / 400	45 / 400	45 / 400	45 / 400	45 / 400	
		Überstandshöhe	Stand Over High	mm	791	798	807	815	825	832	840	848	859	866	876	
		Achsabstand	Wheel Base	mm	1005	1003	1008	1009	1014	1028	1038	1049	1059	1064	1070	
		Slooping °	Slooping °	°	2°	1,5°	1,6°	1,6°	1,4°	1,3°	0,8	0,7°	0,8°	0,2	0,2	
		Reach	Reach	mm	370	370	373	376	378	390	399	406	412	416	418	
		Stack	Stack	mm	529	535	544	551	562	569	574	582	595	599	609	
		Hinterbaubreite	Wide	mm	130	130	130	130	130	130	130	130	130	130	130	130
		Ausfallende	Drop Out		RUS / STD	RUS / STD	RUS / STD	RUS / STD	RUS / STD	RUS / STD	RUS / STD	RUS / STD	RUS / STD	RUS / STD	RUS / STD	RUS / STD

\*\*/\*\* Steuerrohr wählbar/ Headtube selectable

\*\*\*\* BB - Option = Lageraufnahme für BB 30 / Bottom Bracketed Option for BB30

\* konisch Kettenstrebe = conical Chainstays