

KOCMO Road / 2026 KOCMO RR-SKY											
Körpergröße	Body - Size			cm	142-155	155-163	163-172	170-175	175-182	180-188	188-198
Rahmen Größe	Frame Size			cm	XXS-44	XS-49	S-52	M-54	ML-56	L-58	XL-61
Sitzrohr	Seat Tube	Durchmesser	Diameter	mm	31,8	31,8	31,8	31,8	31,8	31,8	31,8
		Länge CTT	Length CTT	mm	440	465	472	489	510	540	570
		Länge CTC	Length CTC	mm	415	435	442	460	480	510	540
		Winkel °	Angle °	°	75.5	75.5	74	74	73.5	73.5	73
Oberrohr	Top Tube	Durchmesser	Diameter	mm	32	32	32	32	32	32	32
		Länge horizontal	Length horizontal	mm	500	509	531	540	560	575	593
Steuerrohr	Head Tube	Durchmesser	Diameter	mm	IS52 - ICR	IS52 - ICR	IS52 - ICR	IS52 - ICR	IS52 - ICR	IS52 - ICR	IS52 - ICR
		Winkel °	Angle °	°	70,75	71,75	72,5	73	73,5	73,5	74
		Länge	Length	mm	99	102	113	130	144	171	192
Unterrohr	Down Tube	Durchmesser	Diameter	mm	45-HydroTube	45-HydroTube	45-HydroTube	45-HydroTube	45-HydroTube	45-HydroTube	45-HydroTube
Sitzstreben	Seat Stay	Durchmesser	Diameter	mm	16	16	16	16	16	16	16
Kettenstreben	Chain Stay	Durchmesser	Diameter		*	*	*	*	*	*	*
		Länge	Length	mm	410	410	410	410	410	410	410
Sattelstütze	Seat Post	Durchmesser	Diameter	mm	27,2	27,2	27,2	27,2	27,2	27,2	27,2
Innenlager	Bottom Bracket	Innenlager-VR-Achse	BB-Center to Front	mm	569	570	574	579	590	605	612
		Innenlager-Absenkung	Bottom Bracket Drop	mm	74	74	74	72	72	72	72
		Gewinde	Threads		T47/68	T47/68	T47/68	T47/68	T47/68	T47/68	T47/68
Rahmen	Frame	Gabelvorlauf / Einbauhöhe	Fork Rake / Mounting Height	mm	45 / 368	45 / 368	45 / 368	45 / 368	45 / 368	45 / 368	45 / 368
		Überstandshöhe	Stand Over High	mm	717	733	742	762	777	804	831
		Achsabstand	Wheel Base	mm	968	969	973	979	989	1004	1011
		Slooping °	Slooping °	°	10,3	7,5	8,3	8,2	7,4	6,9	6,0
		Reach	Reach	mm	368	376	383	387	398	405	411
		Stack	Stack	mm	501	505	518	534	549	575	597
		StR Qutation			1,36	1,34	1,35	1,38	1,38	1,42	1,45
		Hinterbaubreite	Wide	mm	142	142	142	142	142	142	142
Ausfallende	Drop Out		Kocmo X12	Kocmo X12	Kocmo X12	Kocmo X12	Kocmo X12	Kocmo X12	Kocmo X12		

\* Max Tire Size 32 mm

\*\* Di2 / AXS Only

\*\*\* IS52 - ICR = IS52/28.6 | IS52/40